


SUNTECH

CLOSURES

TECHNICAL LT 2021^{PLUS}



Complementary closure solutions to be integrated contemporary Suntech product ranges or existing modern structures

Suntech's innovative Closure product range is serving hi-grade side enclosure solutions that can be integrated between any existing structures or pergola systems.

Closure serie is designed to present accomplished combination of minimal lines and functionality while providing visual optimisation.



Closures

- 007 Sapphire
- 017 Cycle
- 029 Swind
- 039 Violet
- 051 Framee
- 061 Slidia
- 073 Doors
- 079 Vertex
- 089 Wallfix

Closures

SAPPHIRE



A new generation of innovative outdoor protection that expands outdoor living areas with its wide panoramic motorised glass panels with perfectly balanced motorised operation

CYCLE



Customized sleek wide panoramic structural glazing solution

SWIND



Windbreaker - Automatic vertical up-down glass panel

VIOLET



Glass balustrade system with elegant and functional design

FRAMEE



Made of fine-framed aluminum profiles with modern design

SLIDIA



System enables the individual parallel sliding panels to be moved horizontally

VERTEX



Motorised external blind which is extremely durable, practical in use and provides great flexibility for outdoor and indoor living areas

WALLFIX



Aluminium fixed wall privateness with minimal and outstanding design

MORE LUXURY...
MORE PROJECTS...





SAPPHIRE

Explore the stunning new structural glazing solutions with maximized perspectives...

Sapphire is a new generation of innovative outdoor protection that expands outdoor living areas with its wide panoramic motorised glass panels. The system offers a high end fine frame designed guillotine glass system enriched with a perfect combination of luxury and functionality.

The patented worm shaft technology is supported with creative gearing mechanism that provides high level of safety and eliminates the operational problems with maintenance-free mechanism. Systems can incorporate tempered glazing with exclusive frame, glass type and glass color options. Optional two or three panels configurations are available with perfectly balanced motorised operation by remote control. Thanks to strengthened counterweight movement mechanism motor provides balanced up/down operation and panels can be stacked to either upwards or downwards.

System can be configured to fit and cover various types of areas such as restaurants, terraces, wintergardens, balconies either private or commercial. In addition system can be adapted with Suntech range so if there's a Suntech model to suit you can cover any large open area with side glazing options.


Depending on application, panels can be operated & stacked to suit, either upwards or downwards. Alternative opening-stacking configurations provide an infinite range of spacious living area options.

Thanks to multiple stacking positions, fixed panels can also incorporate the function of balustrades. The position of movable panels can be adjusted according to desired height.

Configurations

2 Panels / Down Parking

Standard Tempered Single Glass 8 / 10mm




Internal View

Lateral Section

3 Panels / Down Parking

Standard Tempered Single Glass 8 / 10mm




Internal View

Max. W 4000 > H 3000 mm
Max. W 3000 > H 3500 mm

Lateral Section

Insulated Double Glass 4+12+4 mm (width 2000-3000 mm max.)
5+10+5 mm (width 3000-4000 mm max.)




Internal View

Max. W 4000 > H 2500 mm
Max. W 3500 > H 2750 mm
Max. W 3000 > H 3000 mm

Lateral Section

Insulated Double Glass 4+12+4 mm (width 2000-3000 mm max.)
5+10+5 mm (width 3000-4000 mm max.)



Internal View


Max. W 4000 > H 3000 mm
Max. W 3000 > H 3500 mm

Lateral Section


Configurations

3 Panels / Up Parking


Standard Tempered Single Glass 8 / 10mm



Insulated Double Glass 4+12+4 mm (width 2000-3000 mm max.)



Worm Shaft Technology



- The patented Worm Shaft technology eliminates the trembling and gives smooth movement even on large dimensions with its maintenance-free mechanism.
- This smart technology provides high degree safety compared to other working mechanism based on belts, ropes.
- Gearbox system transfers the movement from the gear to the worm shaft mechanism and ensures the continuation of the movement.
- System has pure balanced up/down operation thanks to strengthened counterweight movement mechanism. Second panel supported by three-wheeled slider and ensures vibration-free movement.
- Depending on application, panels can be operated & stacked either upwards or downwards. Alternative opening-stacking configurations provide various range of spacious living area options.

Order Form

2 Panels

SAPPHIRE

Company Name:

Order Reference:

Order Date:

DIMENSIONS

Width :.....mm

Height :.....mm

Quantity :.....pc

W :.....mm

H :.....mm

Q :.....pc

⋮

⋮

⋮

☐ If panels are in different height,
please provide details.
(H1 ≤ H2)

H1 :.....mm

H2 :.....mm

W

H

Fixed

GLASS TYPES

☐ Single Glass

☐ 8mm

☐ 10mm

☐ Double Glass (4+12+4mm / 5+10+5mm)

☐ Preassembled Frame Without Glass

☐ 8mm

☐ 10mm

☐ 4+12+4mm/5+10+5mm

POWDER-COAT COLORS

RAL colors

☐ 9016

☐ 1013

☐ 9006

☐ 7006

☐ 7016

☐ 9005

Exclusive colors

☐ OGN35

☐ OS561

☐ OY395

☐ OGN39

☐ ON617

☐ ON611

Texture colors

☐ ST9010

☐ ST9001

☐ ST1013

☐ ST7039

☐ ST7016

☐ ST8019

☐ Other ...

GLASS COLORS

☐ TR22 / Transparent

☐ SM33 / Smoked

☐ GN44 / Green

☐ BL55 / Blue

☐ BR66 / Bronze

☐ Other.....

AUTOMATION

☐ SWITCH CONTROL

☐ Inis Keo.....pc

☐ Inis Duo.....pc

☐ REMOTE CONTROL

☐ Telis 1 Pure RTS.....pc

☐ Telis 4 Pure RTS.....pc

☐ Telis 16 Pure RTS.....pc

☐ SMART CONTROL

☐ Situo 1 IO Pure.....pc

☐ Situo 5 IO Pure.....pc

☐ NINA IO.....pc

☐ Thamo New Box.....pc

☐ Connexoon Box.....pc

☐ ADDITIONAL NOTES & DRAWINGS ATTACHED

SUNTECH

rev. 6-05/2021

Order Form

3 Panels

SAPPHIRE

Company Name:

Order Reference:

Order Date:

DIMENSIONS

Width :.....mm

Height :.....mm

Quantity :.....pc

W :.....mm

H :.....mm

Q :.....pc

⋮

⋮

⋮

☐ Down
(H1 ≤ H2 ≤ H3)

☐ Up
(H3 ≤ H2 ≤ H1)

*Available with max. 3000mm width

☐ If panels are in different height,
please provide details.

H1 :.....mm

H2 :.....mm

H3 :.....mm

W

H

H1

H2

H3

GLASS TYPES

☐ Single Glass

☐ 8mm

☐ 10mm

☐ Double Glass (4+12+4mm / 5+10+5mm)

☐ Preassembled Frame Without Glass

☐ 8mm

☐ 10mm

☐ 4+12+4mm/5+10+5mm

POWDER-COAT COLORS

RAL colors

☐ 9016

☐ 1013

☐ 9006

☐ 7006

☐ 7016

☐ 9005

Exclusive colors

☐ OGN35

☐ OS561

☐ OY395

☐ OGN39

☐ ON617

☐ ON611

Texture colors

☐ ST9010

☐ ST9001

☐ ST1013

☐ ST7039

☐ ST7016

☐ ST8019

☐ Other ...

GLASS COLORS

☐ TR22 / Transparent

☐ SM33 / Smoked

☐ GN44 / Green

☐ BL55 / Blue

☐ BR66 / Bronze

☐ Other.....

AUTOMATION

☐ SWITCH CONTROL

☐ Inis Keo.....pc

☐ Inis Duo.....pc

☐ REMOTE CONTROL

☐ Telis 1 Pure RTS.....pc

☐ Telis 4 Pure RTS.....pc

☐ Telis 16 Pure RTS.....pc

☐ SMART CONTROL

☐ Situo 1 IO Pure.....pc

☐ Situo 5 IO Pure.....pc

☐ NINA IO.....pc

☐ Thamo New Box.....pc

☐ Connexoon Box.....pc

☐ ADDITIONAL NOTES & DRAWINGS ATTACHED

SUNTECH

rev. 6-05/2021

013 | 014

Technical Details

2 Panels



Description	Glazing Type
Glazing	Standard 8mm Tempered / Optional 10mm Tempered and 4+12+4mm/5+10+5mm Insulated.
Max. movable glazed frame weight	110kg
Max. height	300cm
Max. width	400cm (Min width :120cm)
Max. size	12 sqm
Surface finish	Electrostatic powder-coating
Motor type	220 VAC 50/60Hz Tubular motor 85NM or 120NM Direct Drive
Control	Switch, remote or smart control options

Description	Glazing Type
Standard Glazing	8mm Tempered Clear Glass
Large Span Glazing	10mm Tempered Clear Glass
Double Insulated Glazing	4mm T + 12mm air gap + 4mm T 5mm T + 10mm air gap + 5mm T

3 Panels



Description	Glazing Type
Glazing	Standard 8mm Tempered / Optional 10mm Tempered and 4+12+4mm/5+10+5mm Insulated.
Max. movable glazed frame weight	220kg
Max. height	350cm
Max. width	400cm (Min width :120cm)
Max. size	12 sqm
Surface finish	Electrostatic powder-coating
Motor type	220 VAC 50/60Hz Tubular motor 85NM or 120NM Direct Drive
Control	Switch, remote or smart control options

Description	Glazing Type
Standard Glazing	8mm Tempered Clear Glass
Large Span Glazing	10mm Tempered Clear Glass
Double Insulated Glazing	4mm T + 12mm air gap + 4mm T 5mm T + 10mm air gap + 5mm T



CYCLE

Adequate comfort of panoramic transparency

Cycle is a vertical guillotine glass system with chain mechanism that is a culmination of this widely utilized modern design concept ensuring maximum transparency and excellent performance with its wide panoramic motorised glass panels.

Flawless design aesthetics offering a smart solution to numerous architectural requirements with simple and contemporary architectural design. The minimal aluminum frame of structure provides availability for an expanded and visually unobstructed perspective.

Cycle can be configured to fit various applications in commercial spaces such as restaurants, hotels, cafes as well as in residential applications.

System features striking elegance and unique facade configurations with its clear and precise lines creating a minimal look and offer a panoramic view in any kind of weather condition.

The movable panels are slid either upwards or downwards and parked behind fixed panel which forms a glass parapet.

Thanks to the full thermal break within the frame and the high specification of glazing used, these guillotine windows have high level of thermal insulation, solar protection and transparency. Different number of glass options are available to provide the needed specific performance.

The system is operated by chain mechanism for ultra-simple control. The motorization of system is fully hidden.


To ensure complete safety, system stops when it meets with an obstacle thanks to smart sensor technology that contributes the safety precautions and make the system highly dependable, durable and performing product.

Additionally smart home automation systems can be integrated as well switch and remote control options, with a touch of a button you can create your desired ambience.

Configurations


2 Panels / Down Parking

Insulated Double Glass 5+11+5 mm



Internal View


Max. W 4000 H 2500 mm
Max. W 3500 H 2750 mm
Max. W 3000 H 3000 mm



Lateral Section


3 Panels / Down Parking

Insulated Double Glass 5+11+5 mm



Internal View


Max. W 4000 H 3000 m
Max. W 3000 H 3500 mm




Lateral Section

3 Panels / Up Parking

Insulated Double Glass 5+11+5 mm




Internal View









Lateral Section



Cycle Guillotine Glass System
Cycle offers a maximum clear span that provides unobstructed view & minimalistic style. The system is operated by just the touch of button.





Order Form

2 Panels

CYCLE

Company Name:

Order Reference:

Order Date:

DIMENSIONS

Width :.....mm

Height :.....mm

Quantity :.....pc

W :.....mm

H :.....mm

Q :.....pc

⋮

⋮

⋮

☐ If panels are in different height,
please provide details.
($H1 \leq H2$)

H1 :.....mm

H2 :.....mm

W

H

Fixed

GLASS OPTION

☐ With Glass

☐ Preassembled Frame Without Glass
(5+11+5mm)

POWDER-COAT COLORS

RAL colors

Exclusive colors

Texture colors

☐ 9016

☐ 1013

☐ 9006

☐ 7006

☐ 7016

☐ 9005

☐ OGN35

☐ OS561

☐ OY395

☐ OGN39

☐ ON617

☐ ON611

☐ ST9010

☐ ST9001

☐ ST1013

☐ ST7039

☐ ST7016

☐ ST8019

☐ Other ...

GLASS COLORS

☐ TR22 / Transparent

☐ SM33 / Smoked

☐ GN44 / Green

☐ BL55 / Blue

☐ BR66 / Bronze

☐ Other.....

AUTOMATION

☐ SWITCH CONTROL

☐ Inis Keo.....pc

☐ Inis Duo.....pc

☐ REMOTE CONTROL

☐ Telis 1 Pure RTS.....pc

☐ Telis 4 Pure RTS.....pc

☐ Telis 16 Pure RTS.....pc

☐ SMART CONTROL

☐ Situo 1 IO Pure.....pc

☐ Situo 5 IO Pure.....pc

☐ NINA IO.....pc

☐ Thamo New Box.....pc

☐ Connexoon Box.....pc

OPTIONAL

☐ SAFETY SENSOR

☐ ADDITIONAL NOTES & DRAWINGS ATTACHED

SUNTECH

rev. 6-05/2021

Order Form

3 Panels

CYCLE

Company Name:

Order Reference:

Order Date:

DIMENSIONS

Width :.....mm

Height :.....mm

Quantity :.....pc

W :.....mm

H :.....mm

Q :.....pc

⋮

⋮

⋮

☐ Down
($H1 \leq H2 \leq H3$)

☐ Up
($H3 \leq H2 \leq H1$)
*Available with max. 3000mm width

☐ If panels are in different height,
please provide details.

H1 :.....mm

H2 :.....mm

H3 :.....mm

W

H

H1

H2

H3

GLASS OPTION

☐ With Glass

☐ Without Glass

* Glass is 5+11+5MM

POWDER-COAT COLORS

RAL colors

Exclusive colors

Texture colors

☐ 9016

☐ 1013

☐ 9006

☐ 7006

☐ 7016

☐ 9005

☐ OGN35

☐ OS561

☐ OY395

☐ OGN39

☐ ON617

☐ ON611

☐ ST9010

☐ ST9001

☐ ST1013

☐ ST7039

☐ ST7016

☐ ST8019

☐ Other ...

GLASS COLORS

☐ TR22 / Transparent

☐ SM33 / Smoked

☐ GN44 / Green

☐ BL55 / Blue

☐ BR66 / Bronze

☐ Other.....

AUTOMATION

☐ SWITCH CONTROL

☐ Inis Keo.....pc

☐ Inis Duo.....pc

☐ REMOTE CONTROL

☐ Telis 1 Pure RTS.....pc

☐ Telis 4 Pure RTS.....pc

☐ Telis 16 Pure RTS.....pc

☐ SMART CONTROL

☐ Situo 1 IO Pure.....pc

☐ Situo 5 IO Pure.....pc

☐ NINA IO.....pc

☐ Thamo New Box.....pc

☐ Connexoon Box.....pc

OPTIONAL

☐ SAFETY SENSOR

☐ ADDITIONAL NOTES & DRAWINGS ATTACHED

025 | 026

Technical Details

2 Panels



Description	Glazing Type
Glazing	5+11+5mm Insulated.
Max. movable glazed frame weight	110kg
Max. height	300cm
Max. width	400cm (Min width :120cm)
Max. size	12 sqm
Surface finish	Electrostatic powder-coating
Motor type	220 VAC 50/60Hz Tubular motor 85NM or 120NM Direct Drive
Control	Switch, remote or smart control options

Description	Glazing Type
Double Insulated Glazing	5mm T + 11mm air gap + 5mm T

3 Panels



Description	Glazing Type
Glazing	5+11+5mm Insulated.
Max. movable glazed frame weight	220kg
Max. height	350cm
Max. width	400cm (Min width :120cm)
Max. size	12 sqm
Surface finish	Electrostatic powder-coating
Motor type	220 VAC 50/60Hz Tubular motor 85NM or 120NM Direct Drive
Control	Switch, remote or smart control options

Description	Glazing Type
Double Insulated Glazing	5mm T + 11mm air gap + 5mm T



SWIND Windbreaker

Definition of outdoor areas with wider panoramas

Swind has a simple and functional wind breaker design concept that expands your terrace, patio or open-air spaces to shield outdoor living areas by offering adequate wind breaking with the option of total transparency.

System is mostly preferred at restaurants, cafes and terraces either private or commercial as an automatic vertical up-down glass separator for outdoor spaces, besides fixed panel can also incorporate the function of balustrade. Thanks to led stripe dimmer lighting integrated side frame the fixed panel assigns distinctive appeal.


The system is modular and completely flexible as there are no limits in the horizontal direction that can be used to surround spaces of all types and sizes. There are no vertical struts between moveable and fix panels that provides unobstructed view. The modules can be moved up-down individually or in groups by remote control and the position of movable panels can be adjusted according to desired height. The system can be fixed on the ground or can be portable with the wheeled base option, also a decorative harmony can be ensured with plant pot integration.



Led Stripe Dimmer Ligting illuminates all around the system and creates a warm atmosphere. Dimmable Soft Led Stripe lighting on sides within the structure provides intensity of day light or cool white options.


■ Led Stripe Dimmer Lighting

Section Details




Configurations


H70




H80



H90



H100



Company Name:
Order Reference:

Order Date:

CONFIGURATIONS

- ☐ H70
- ☐ H80
- ☐ H90
- ☐ H100

DIMENSIONS

Width :.....mm

Quantity :.....pc

W :.....mm

Q :.....pc

.


.

.

.

* Fixed panel is 10mm single, movable panel is 8mm single tempered glass

- ☐ With Glass
- ☐ Without Glass



POWDER-COAT COLORS

RAL colors	Exclusive colors	Texture colors	
<input type="checkbox"/> 9016	<input type="checkbox"/> OGN35	<input type="checkbox"/> ST9010	<input type="checkbox"/> Other ...
<input type="checkbox"/> 1013	<input type="checkbox"/> OS561	<input type="checkbox"/> ST9001	
<input type="checkbox"/> 9006	<input type="checkbox"/> OY395	<input type="checkbox"/> ST1013	
<input type="checkbox"/> 7006	<input type="checkbox"/> OGN39	<input type="checkbox"/> ST7039	
<input type="checkbox"/> 7016	<input type="checkbox"/> ON617	<input type="checkbox"/> ST7016	
<input type="checkbox"/> 9005	<input type="checkbox"/> ON611	<input type="checkbox"/> ST8019	

GLASS COLORS

- ☐ TR22 / Transparent
- ☐ SM33 / Smoked
- ☐ GN44 / Green
- ☐ BL55 / Blue
- ☐ BR66 / Bronze
- ☐ Other.....

OPTIONAL

- ☐ Led Stripe Dimmer Lighting
- ☐ Cool White - 5100K
- ☐ Day Light - 2800K
- ☐ Ground Installation (Inox)
- ☐ Portable Wheeled Base
- ☐ Plant Pot
- ☐ Plant Pot Portable Wheeled Base

AUTOMATION

- ☐ SWITCH CONTROL
- ☐ REMOTE CONTROL
- ☐ Inis Keo.....pc
- ☐ Telis 1 Pure RTS.....pc
- ☐ Inis Duo.....pc
- ☐ Telis 4 Pure RTS.....pc
- ☐ Telis 16 Pure RTS.....pc

☐ ADDITIONAL NOTES & DRAWINGS ATTACHED

Technical Details



Glazing	Fixed panel 10 mm tempered single glass Up-down panel 8 mm tempered single glass
Max. width for single module	2000 mm
Max. height for single module	1000 mm (fixed) + 700 mm (up-down)
Max. movable glazed frame weight	50 kg
Fixed panel glass dimension	10 mm single tempered
Movable panel glass dimension	8 mm single tempered
Frame profile dimension	134x73 mm
Surface finish	Electrostatic powder-coating
Motor type	220 VAC 50 Hz double shaft direct drive
Control system	Switch, remote control options
Automation	included
Control Unit	optional
Led Stripe Dimmer lighting	optional
Ground installation (inox)	optional
Wheeled base	optional
Plant pot	optional



VIOLET

Minimal separation way for exteriors...

Violet is a glass balustrade system that can be applied in various application areas with its modern and minimalistic design. System provides the simplicity and elegance demanded by today's world at the same time and creates an effective solution with its straight lines. It is both a safety barrier and protects your living space against wind and various other elements.

When the clean lines of the glass balustrade match with the modern finish it will enable you to have experience of the glass elegance by providing the optimum result as an architectural solution.

Thanks to its transparent appearance, it does not create an obstacle between inside and outside and protects you against external influences with its strong protection effect.

Multiple modules that come side by side with sandwich panel structure and optional handrail preference give you the choice to cover a wider area. With a maximum width of 6 m and a height of 1 m, it can be used comfortably in many different areas such as balcony, terrace, pool side, patio, garden, restaurant and cafe.

Violet is an ideal option for structural glass solutions that creates no obstruction insight through a space with a minimal contemporary finish throughout for use as frameless balustrades.

The stylish lighting solution that can be integrated into the system creates distinguished features.


It enables you to design a minimal, aesthetically neat and functional glass barrier between levels with no visible fixings.





Led Stripe Dimmer Ligting illuminates all around the system and creates a warm atmosphere. Dimmable Soft Led Stripe lighting on sides within the structure provides intensity of day light or cool white options.

■ Led Stripe Dimmer Lighting

Section Details




Accessories & Optionals



Installation & Base Options



Compact & Easy Assembly

The system reaches its compact outlook with simple and quick installation steps.






Smooth Edge Connection

Clean appearance in the corner points.



Configurations



One Module
1000<2000mm

Two Modules
2000<4000mm

Three Modules
4000<6000mm

Order Form

VIOLET

Company Name:
Order Reference:

Order Date:

CONFIGURATIONS

- ☐ H70
- ☐ H80
- ☐ H90
- ☐ H100

DIMENSIONS

Width :.....mm


Quantity :.....pc

W :.....mm

Q :.....pc

.

.



If modules are multiple and each module is in different width, please provide details (max. width for single module is 2000 mm, double modules 4000 mm, triple modules 6000 mm)

W1 cm
W2 cm
W3 cm

GLASS OPTION

- ☐ With Glass
- ☐ Without Glass

* Glass is 8MM+1,52PVP+8MM

POWDER-COAT COLORS

RAL colors	Exclusive colors	Texture colors	
<input type="checkbox"/> 9016	<input type="checkbox"/> OGN35	<input type="checkbox"/> ST9010	<input type="checkbox"/> Other ...
<input type="checkbox"/> 1013	<input type="checkbox"/> OS561	<input type="checkbox"/> ST9001	
<input type="checkbox"/> 9006	<input type="checkbox"/> OY395	<input type="checkbox"/> ST1013	
<input type="checkbox"/> 7006	<input type="checkbox"/> OGN39	<input type="checkbox"/> ST7039	
<input type="checkbox"/> 7016	<input type="checkbox"/> ON617	<input type="checkbox"/> ST7016	
<input type="checkbox"/> 9005	<input type="checkbox"/> ON611	<input type="checkbox"/> ST8019	

GLASS COLORS

- ☐ TR22 / Transparent
- ☐ SM33 / Smoked
- ☐ GN44 / Green
- ☐ BL55 / Blue
- ☐ BR66 / Bronze
- ☐ Other.....

OPTIONAL

- ☐ Led Stripe Dimmer Lighting
- ☐ Handrail
- ☐ Cool White
- ☐ Day Light

LIGHTING OPERATION

- ☐ SWITCH CONTROL
- ☐ REMOTE CONTROL
- ☐ Inis Keo.....pc
- ☐ Telis 1 Pure RTS.....pc
- ☐ Inis Duo.....pc
- ☐ Telis 4 Pure RTS.....pc
- ☐ Telis 16 Pure RTS.....pc

☐ ADDITIONAL NOTES & DRAWINGS ATTACHED

Technical Details



Glazing	8+1.52 pvb+8 mm laminated glass
Max. size for single system	6000x1000 mm (three modules)
Max. width for single module	2000 mm
Max. height for single module	1000 mm
Aluminum base profile	70x95 mm
Surface finish	Electrostatic powder-coating
Lighting operation	Switch, remote control options
Automation	N/A
Led Stripe Dimmer lighting	optional
Control unit	optional
Hand rail	optional

* N/A (not available)




FRAMEE

Framee is sliding glass system with fine-framed double glazed panels


System is made of fine-framed aluminum profiles with modern design & suitable especially for large-area applications and completed with stylish and functional accessories perfectly matching with modern architectural living spaces. System offers a comfortable sliding with silent movement and allows individual sliding panels to be moved horizontally to one side or both in parallel.

Framee provides reinforced profile designs for customized static values, condensated frame profile design as well as glazing up to 26mm thickness.

System is ease of install with compact connection details.




Stainless steel bottom rail for easy and smooth movement




6+12+6mm tempered insulated double glass

Technical Specifications	Measurements		
System Depth	Frame	81,7/112,6/181,7 mm	
	Sash	38 mm	
Air Permeability	Opening Sash	24 mm	
* Take double glazing thickness tolerances into consideration.			
Performance Criteria	Classification	Test Standards	
Thermal Transm. Coeff.*	-	-	
Air Permeability	Class 8A (450 Pa)	EN 1026 EN 12207	
Water Tightness	Class 4 (600 Pa)	EN 1027 EN 12208	
Resistance to Wind	Class B2 (800 Pa)	EN 12210	


* Special condensation calculations for the project were separately carried out.
** Please contact us to obtain reports that contain the relevant performance values.



Handles & Lock Positions



Handles & Lock Types





Anodising Brushed Color Options





From natural and metallic to anodizing brushed color options give a sleek and elegant finish to systems.

Single Slide



2 Rails 2 Panels



3 Rails 3 Panels





4 Rails 4 Panels





Double Slide



2 Rails 4 Panels



3 Rails 6 Panels



4 Rails 8 Panels



Company Name:
Order Reference:

Order Date:

QUANTITY: pc

DIMENSIONS


W - Width :.....mm
H - Height :.....mm

GLASS OPTION

☐ With Glass
☐ Without Glass

* Glass is 6+12+6MM

PANEL TYPES



POWDER-COAT COLORS

RAL colors

☐ 9016
☐ 1013
☐ 9006
☐ 7006
☐ 7016
☐ 9005

Exclusive colors

☐ OGN35
☐ OS561
☐ OY395
☐ OGN39
☐ ON617
☐ ON611

Texture colors

☐ ST9010
☐ ST9001
☐ ST1013
☐ ST7039
☐ ST7016
☐ ST8019

☐ Other ...

GLASS COLORS

☐ TR22 / Transparent

☐ SM33 / Smoked

☐ GN44 / Green

☐ BL55 / Blue

☐ BR66 / Bronze

☐ Other.....

HANDLE & LOCK TYPES

☐ Handle with Click Lock (Standard)

☐ Handle with Click & Key Lock

HANDLE COLORS


☐ Natural

☐ Metallic

☐ Black

(Anodising brushed)

HANDLE POSITION



☐ ADDITIONAL NOTES & DRAWINGS ATTACHED

Technical Details



Glazing	6+12+6 mm insulated double glass
Slide Options	2,3 or 4 panels single slide 4,6 or 8 panels double slide
Max. width for single slide	6000 mm
Max. width for double slide	7000 mm
Max. height	3000 mm
Max. load capacity per panels	240 kg
System depth	Frame 81 mm Sash 38 mm
Surface finish	Electrostatic powder-coating
Control system	Manual
Inner handle with click lock	included
Inner handle with hidden lock	included
Outer handle	included



SLIDIA





Give modern appeal and depth to spaces...

Slidia is a stylish and practical closing solution that can be integrated into structures and presents you indoor coziness along with outdoor coolness.





Sliding system enables the individual parallel sliding panels to be moved horizontally. By opening and closing of first sliding panel, the other sliding panels are automatically opened and closed by integrated subsequent panels. The floor-mounted construction means that a wide open area can be covered without additional roof supports.

The bottom wheel carriages ensure optimum and smooth running of the individual sliding panels. Height compensation of the ceiling rail up to 20 mm and height adjustment of the rollers up to 5 mm allows the sliding system to compensate for potential subsidence in the eaves or a lintel easily.

The sliding glass can be easily matched with attractive look you aspire with variety of rail and panel types. The system can be slided to one side or both sides as you desire.





Slide Direction - Single Side





Slide Direction - Double Side



3 Rails 4 Panels





5 Rails 8 Panels



3 Rails 6 Panels




5 Rails 10 Panels






Single Glass Handle Types


Flush Circle Handle



Sliding Glass Lock Types



Push & Pull Bar



Order Form

Company Name:
Order Reference:

Order Date:


DIMENSIONS

Width :.....mm Height :.....mm Quantity :.....pc
W :.....mm H :.....mm Q :.....pc
: : :
: : :

GLASS OPTION


☐ With Glass
☐ Without Glass
* Glass is 8MM

PANEL TYPES



SLIDE DIRECTIONS

Single Side
☐ RX to LX
☐ LX to RX



Double Side
*Center to RX and LX

POWDER-COAT COLORS

RAL colors	Exclusive colors	Texture colors	<input type="checkbox"/> Other ...
<input type="checkbox"/> 9016	<input type="checkbox"/> OGN35	<input type="checkbox"/> ST9010	
<input type="checkbox"/> 1013	<input type="checkbox"/> OS561	<input type="checkbox"/> ST9001	
<input type="checkbox"/> 9006	<input type="checkbox"/> OY395	<input type="checkbox"/> ST1013	
<input type="checkbox"/> 7006	<input type="checkbox"/> OGN39	<input type="checkbox"/> ST7039	
<input type="checkbox"/> 7016	<input type="checkbox"/> ON617	<input type="checkbox"/> ST7016	
<input type="checkbox"/> 9005	<input type="checkbox"/> ON611	<input type="checkbox"/> ST8019	

HANDLE TYPE

☐ Flush Circle Handle
☐ Push & Pull Bar
☐ Round Bar
☐ Square Bar


PANEL INSULATION TYPE

☐ Transparent Gasket
☐ Transparent Gasket with Brush
☐ Aluminum Slat with Brush

GLASS COLORS

☐ TR22 / Transparent
☐ SM33 / Smoked
☐ GN44 / Green
☐ BL55 / Blue
☐ BR66 / Bronze
☐ Other.....

HANDLE POSITION



H:.....cm
*Standard height value is 110 cm.


☐ ADDITIONAL NOTES & DRAWINGS ATTACHED

Technical Details




Glazing	8 mm tempered single glass
Slide Options	2,3 or 4 panels single slide 4,6,8 or 10 panels double slide
Max. width for single slide	6000 mm
Max. width for double slide	7200 mm
Max. height	2800 mm
Max. load capacity per panels	80 kg
Surface finish	Electrostatic powder-coating
Control system	Manual
Flush circle handle or push&pull bar	included
Lock	included


Glass Door




Single Slide (Hinged)



Single Slide (Hydraulic)




Double Slide (Hinged)




Double Slide (Hydraulic)


Frame Door




Single Slide (Hinged)



Single Slide (Hydraulic)




Double Slide (Hinged)



Double Slide (Hydraulic)


Sliding Glass Handle Types

Push & Pull Bar




Sliding Glass Lock Types


Square Floor Installed



Photocell Door



Single Slide



Double Slide

Only movable panels are included. Fixed panels are not included.

GLASS DOOR

Single Slide (Hinged)	1.217 €
Double Slide (Hinged)	2.435 €
Single Slide (Hydraulic)	1.311 €
Double Slide (Hydraulic)	2.623 €

FRAME DOOR

Single Slide (Hinged)	1.405 €
Double Slide (Hinged)	2.810 €
Single Slide (Hydraulic)	1.968 €
Double Slide (Hydraulic)	3.933 €

PHOTOCELL DOOR

Single Slide	5.152 €
Double Slide	5.620 €

Notes:
Prices are Ex-Works.
Handles and Locks are included for Glass and Frame Doors.
Standard color is transparent glass, for other options net +14€/m² price difference will be charged.
Packing Cost:
Wooden crate cost is net 221€.

Order Form

GLASS DOOR

Company Name:
Order Reference:

Order Date:
Quantity:

DOOR TYPE

- ☐ Single Panel
☐ Double Panel



DIMENSIONS

W - Width :.....mm
H - Height :.....mm

GLASS TYPE

*Single Glass (10mm)

PANEL TYPES



*Outer view

SLIDE DIRECTIONS


Single Side Direction



☐ to LX

☐ to RX

Double Side Direction



*Center to RX and LX

*Outer view

POWDER-COAT COLORS

RAL
colors

- ☐ 9016
☐ 1013
☐ 9006
☐ 7006
☐ 7016
☐ 9005

Exclusive
colors

- ☐ OGN35
☐ OS561
☐ OY395
☐ OGN39
☐ ON617
☐ ON611

Texture
colors

- ☐ ST9010
☐ ST9001
☐ ST1013
☐ ST7039
☐ ST7016
☐ ST8019

☐ Other ...

HANDLE TYPE

- ☐ Flush Circle Handle
☐ Push & Pull Bar
☐ Round Bar
☐ Square Bar


LOCK TYPE

- ☐ Key Lock
☐ Square Floor Installed
☐ Round Center Installed
☐ Allen Lock
☐ Square Floor Installed
☐ Round Center Installed

GLASS COLORS

- ☐ TR22 / Transparent
☐ SM33 / Smoked
☐ GN44 / Green
☐ BL55 / Blue
☐ BR66 / Bronze
☐ Other.....

HANDLE POSITION



H:.....cm

*Standard height value is
110 cm.

☐ ADDITIONAL NOTES & DRAWINGS ATTACHED

*Price will be determined according to project details.

Order Form

FRAME DOOR

Company Name:

Order Date:

Order Reference:

Quantity:

DOOR TYPE

☐ Single Panel

☐ Double Panel

DIMENSIONS

W - Width :.....mm

H - Height :.....mm

GLASS TYPES

*Double Glass (4+11+4 mm)

Single Slide

W

H

LX

RX

Double Slide

W

H

LX

RX

OPENING DIRECTIONS

Single Side Direction

LX

RX

☐ to LX

☐ to RX

Double Side Direction

LX

RX

*Center to RX and LX

*Outer view

SELF CLOSING

☐ Without Closing Mechanism

☐ With Closing Mechanism

☐ In

☐ Out

POWDER-COAT COLORS

RAL colors

Exclusive colors

Texture colors

☐ 9016

☐ 1013

☐ 9006

☐ 7006

☐ 7016

☐ 9005

☐ OGN35

☐ OS561

☐ OY395

☐ OGN39

☐ ON617

☐ ON611

☐ ST9010

☐ ST9001

☐ ST1013

☐ ST7039

☐ ST7016

☐ ST8019

☐ Other ...

GLASS COLORS

☐ TR22 / Transparent

☐ SM33 / Smoked

☐ GN44 / Green

☐ BL55 / Blue

☐ BR66 / Bronze

☐ Other.....

HANDLE - LOCK TYPE

☐ Pull Handle / Lock

☐ Handle Without Lock

☐ Handle With Key Lock

☐ Handle With Allen Lock

☐ Push & Pull Bar

☐ Round Bar

☐ Square Bar

HANDLE POSITION

H

H

H:.....cm

*Standard height value is 110 cm.

☐ ADDITIONAL NOTES & DRAWINGS ATTACHED

*Price will be determined according to project details.

Order Form

PHOTOCELL DOOR

Company Name:

Order Date:

Order Reference:

Quantity:

DOOR TYPE

☐ Single Panel

☐ Double Panel

DIMENSIONS

W - Width :.....mm

H - Height :.....mm

GLASS TYPES

*Laminated Glass (4+4 mm)

Single Slide

W

H

LX

RX

Double Slide

W

H

LX

RX

SLIDE DIRECTIONS

Single Side Direction

☐ RX to LX

☐ LX to LX

Double Side Direction

*Center to RX and LX

POWDER-COAT COLORS

RAL colors

Exclusive colors

Texture colors

☐ 9016

☐ 1013

☐ 9006

☐ 7006

☐ 7016

☐ 9005

☐ OGN35

☐ OS561

☐ OY395

☐ OGN39

☐ ON617

☐ ON611

☐ ST9010

☐ ST9001

☐ ST1013

☐ ST7039

☐ ST7016

☐ ST8019

☐ Other ...

GLASS COLORS

☐ TR22 / Transparent

☐ SM33 / Smoked

☐ GN44 / Green

☐ BL55 / Blue

☐ BR66 / Bronze

☐ Other.....

CONTROL TYPE

☐ Double Sided Transition

☐ One Side Button

☐ Double Side Button

☐ ADDITIONAL NOTES & DRAWINGS ATTACHED

*Price will be determined according to project details.

SUNTECH

rev. 6-05/2021

077 | 078



VERTEX ZIP SYSTEM

Aesthetical privacy with hi-tech functions...

New Series Vertex Zip Screens are designed to represent solutions of aesthetic appeal and contemporary complement with its unique fabric guide technology concealed within the side channels.

Vertex is motorised external blind which is extremely durable, practical in use and provides great flexibility for outdoor and indoor living areas. System can be integrated for increased functionality of spaces such as restaurants, terraces, balconies, either private or commercial. Simple and stylish design of the system means it can be incorporated into new or existing buildings and Suntech systems with an extensive range of frame and fabric colour options.

Minimal slimline design of Vertex 95 fits in Eva model perfectly. Vertex 130 serie is ideal solution for Suntech Standard LT & XL models. Vertex 150 is developed to function in a complementary manner with Privée models.

This extensive serie is redefined the simple design for minimal look characterised by architectural demands. The zip external blinds are engineered for ease of installation, flexible application and long durability.

Furthermore the patented locking mechanism secures the fabric in the lower position which ensures even tension on fabric and fully hidden motorisation system allows ultimate control of your living space with a single touch.

Thanks to large range of fabric options system provides maximum protection against solar radiation and penetration of heat while preserving the optimal level of natural light in the interior and contact with environment. The production technology of fabrics ensures a high resistance to external influences such as wind or changes in temperature and humidity.

Thanks to clever interlocking parts and self-aligning side channels, each system offers a perfect fitting from edge to edge with no gaps and provides a stylish and simple finish. It also has specially designed zipper which is welded to the edges of the fabric to create seamless operation and control of sunlight. The zipper is securely held in the side channels which allows the fabric to run freely and quietly while preventing the fabric to pull out of the channel.



The minimalist, slimline, contemporary design of the zip system provides comfortable shade and protects against the UV rays. The system includes motorised painted aluminium structure, entirely powder-coated with stainless steel bolts and screws.

Vertex 95 Zip System




Vertex 130 Zip System




Vertex 150 Zip System



Section Details



Configurations



Order Form

VERTEX ZIP SYSTEM

Company Name:
Order Reference:


Order Date:

MODEL

- ☐ 95
☐ 130
☐ 150

DIMENSIONS

Width :.....mm Height :.....mm Quantity :.....pc
W :.....mm H :.....mm Q :.....pc
: : :
: : :



POWDER-COAT COLORS

RAL colors Exclusive colors Texture colors ☐ Other ...

☐ 9016 ☐ OGN35 ☐ ST9010
☐ 1013 ☐ OS561 ☐ ST9001
☐ 9006 ☐ OY395 ☐ ST1013
☐ 7006 ☐ OGN39 ☐ ST7039
☐ 7016 ☐ ON617 ☐ ST7016
☐ 9005 ☐ ON611 ☐ ST8019

FABRIC COLORS

☐ SOLTIS 86 ☐ SOLTIS W92
CODE..... CODE.....

☐ SOLTIS 96 ☐ SOLTIS W96
CODE..... CODE.....

☐ CRYSTAL

SYSTEM POSITION

☐ OUT ☐ IN

Pointview


Out In

CABLE OUT

☐ TOP ☐ SIDE ☐ BOTTOM

MOTOR SIDE

☐ LEFT ☐ RIGHT



AUTOMATION

☐ SWITCH CONTROL ☐ REMOTE CONTROL ☐ SMART CONTROL

☐ Inis Keo.....pc ☐ Telis 1 Pure RTS.....pc ☐ Situo 1 IO Pure.....pc
☐ Inis Duo.....pc ☐ Telis 4 Pure RTS.....pc ☐ Situo 5 IO Pure.....pc
☐ Telis 16 Pure RTS.....pc ☐ NINA IO.....pc
☐ Thamo New Box.....pc
☐ Connexoon Box.....pc

☐ ADDITIONAL NOTES & DRAWINGS ATTACHED

Technical Details



Box dimensions	Vertex 95 - 95x120 mm Vertex 130 - 130x140 mm Vertex 150 - 150x150 mm
Max. width for single module	Vertex 95 5000 mm / Vertex 130&150 6000 mm
Max. height for single module	Vertex 95 3000 mm / Vertex 130&150 4000 mm
Puller profile dimension	36,5x37,5 mm
Rafter profile dimension	54x40 mm
Surface finish	Electrostatic powder-coating
Motor type	220 VAC 50Hz tubular motor 20,30 or 40 NM direct drive
Control system	Switch, remote or smart control options
Automation	included
Control Unit	optional
* Fabric	Standard *Ferrari Soltis Horizon 86 Fabric
* Optional fabric types	*Ferrari Soltis Lounge 96, Perform 92, Proff W96 Fabric Crystal (Transparent) Fabric

WALLFIX

Privilege of aesthetical privacy with a stylish look

Wallfix is an aluminium fixed side enclosure that adds privacy whilst enhancing visual appeal and offer a luxurious compliment to Suntech models and highlight design of any outdoor areas.

Simple and elegant lines of Wallfix are compatible with the modern finishes of application areas, it will enable you to have a specific privacy by aluminium fixed wall which is perfect for seamlessly addition to Suntech's architectural models or any independent open spaces.

Wallfix enables you to achieve complete control over shade which adds a unique amenity to your outside areas with invisible fixings.

System highlights attractive aspect of the design by amplifying overall aesthetic of Suntech models with perfect combination ensures comfort and reliefment.





Wallfix Fixed Side Enclosure
The unique designed privacy of Wallfix side enclosure can be combined with Aerolux bioclimatic system to optimise outdoor living areas visually.



Configurations

Dimensions
Width min. 1000mm - max. 6000mm
Height min. 1000mm - max. 4000mm



Order Form

WALLFIX

Company Name:
Order Reference:

Order Date:

DIMENSIONS

Width :.....mm Quantity :.....pc
W :.....mm Q :.....pc
:
:




POWDER-COAT COLORS

RAL colors	Exclusive colors	Texture colors	
<input type="checkbox"/> 9016	<input type="checkbox"/> OGN35	<input type="checkbox"/> ST9010	<input type="checkbox"/> Other ...
<input type="checkbox"/> 1013	<input type="checkbox"/> OS561	<input type="checkbox"/> ST9001	
<input type="checkbox"/> 9006	<input type="checkbox"/> OY395	<input type="checkbox"/> ST1013	
<input type="checkbox"/> 7006	<input type="checkbox"/> OGN39	<input type="checkbox"/> ST7039	
<input type="checkbox"/> 7016	<input type="checkbox"/> ON617	<input type="checkbox"/> ST7016	
<input type="checkbox"/> 9005	<input type="checkbox"/> ON611	<input type="checkbox"/> ST8019	

☐ ADDITIONAL NOTES & DRAWINGS ATTACHED


Technical Details



Max. width for single module	6000 mm
Max. height for single module	4000 mm
Louvre dimension	200 mm
Louvre quantity in max. size	20 pcs

ALUMINUM

basic




RAL 9016



RAL 1013




RAL 9006



RAL 7006



RAL 7016



RAL 9005

exclusive



OGN35



OS561



OY395



OGN39



ON617



ON611

texture



ST9010




ST9001



ST1013



ST7039



ST7016



ST8019

Glass Colors



TR22 / Transparent



SM33 / Smoked



GN44 / Green



BL55 / Blue



BR66 / Bronze

The color and gloss level shown in this color swatch should be used only as a guide.
All ral colors are available.

PRICES

All prices in Euro exclude VAT and transport cost, but include all material cost with packaging in bubble wrap.

PRICE LIST

The price lists are effective as of 01.09.2021 and Albayrak has rights to modify the price lists in at any time with a 30 day notice.

TRANSPORT

Goods will be supplied EXW and therefore all costs for transport from the Manufacturer's seat to the Purchaser's destination shall be at full charge of the Purchaser, who will also provide an insurance policy covering all risks for damage or loss of goods during transport.

ALBAYRAK

Delivery terms of contractual products are as follows: Approximately four-six weeks (changeable according to order content or quantity) which will be communicated to the Purchaser at the time of the order weeks from the receiving deposit payment.

INVOICING PROCEDURE

The Invoicing Procedure (in Euro currency) will be according to the Manufacturer's standards.

WARRANTY OF QUALITY

Albayrak warrants that all items shall be free of all defects relating to 5 years structure&coating, 2 years mechanics, 2 years automation and 2 years lighting after delivery. The warranty does not cover the misuse of the goods. The time of the warranty of the product will last for five year and shall commence from the last date of delivery of the Goods. Albayrak must rectify any defects in the Goods which are apparent within a reasonable time. If the Albayrak fails to rectify any defect within a reasonable time for rectification, the Purchaser may engage third parties to perform the rectification. In such case the cost of rectification will be paid by the Albayrak.

WARRANTY BY ALBAYRAK

Albayrak warrants that:

- Albayrak has the right to sell the Goods, which are free from any charge or encumbrance;
- The Goods will be fit for the purpose for which goods of that kind are commonly used and any other purposes made known expressly or by implication to the Albayrak by the Purchaser;
- The Goods will be of merchantable quality and free from defects in material

PACKAGING AND MARKINGS

All proper care and protection must be given and provided by the Albayrak in ensuring against possible damage or breakage in transit. Albayrak is to package all items suitable for transport. The package will be made according to the Albayrak's standard. Albayrak must supply the Goods in a competent and professional manner and comply with all directions from the Purchaser.

DELIVERY TERMS

Albayrak undertakes to deliver the Goods at his own seat in Istanbul – Turkey according to the agreed delivery time. All deliveries shall be accompanied by a fully detailed delivery documents as per the Albayrak's standards. Immediately after receipt of goods, anyhow not later than 10 days from receipt the Purchaser is obliged to inspect goods fully and in detail and notify to Albayrak any defects immediately. Failure in doing so will prevent the Purchaser to issue any claim against Albayrak for defects. Title to and risk in the Goods pass to the Purchaser upon final and full payment of goods delivered. Goods must be delivered during normal hours unless alternative arrangements have been made with the Purchaser.

MISCELLANEOUS

The law applicable to the merits of the dispute shall be United Nations Convention on Contracts for the International Sale of Goods dated 11 April 1980. In case United Nations Convention on Contracts for the International Sale of Goods dated 11 April 1980 does not include any rules governing the dispute arising between the parties, Turkish law will be applied.

suntechoutdoor.com



suntechoutdoor.com